optimize! softing

SPLICEXPERT

FiberFox MINI6S+

Compact and fully automatic fusion splicer

FEATURES

- AOCAT core alignment (Automatic Optical Core Analysis & Tracking System)
- 4.3″ color LCD touchscreen
- LED injection system (no mirrors)
- Special magnetic interchangeable holders for easy setup
- Fast splice time - 6 seconds

The SpliceXpert FiberFox MINI6S+ offers excellent value for money while ranking among the most powerful and durable fusion splicers on the market. With its water-resistant, dustproof, and shockproof design, it ensures reliable performance even in harsh environments.

The automatic and precise fiber core alignment, powered by the AOCAT system (Automatic Optical Core Analysis & Tracking) enables fast splicing in as little as 6 seconds.

The MINI6S+ is supplied with an extensive accessory package, including two rechargeable batteries and a crimp splice press with dedicated holder. The interchangeable fiber holders simplify the splicing process and can also be used with the included high-end cleaver, providing maximum flexibility in the field.



SCAN ME

IT Networks

itnetworks.softing.com/fiberfox-mini-6s

FiberFox MINI6S+

TECHNICAL SPECIFICATIONS

SPLICING	
Method	High-end core alignment (AOCAT: Automatic Optical Core Analysis & Tracking System)
Average splice loss	SM (0.01 dB) MM (0.01 dB) DS (0.04 dB) NZDS (0.04 dB) RL: >>60 dB
Splice time	Quick: 6 s / SM auto: 10 s
Modes	166 modes (pre-set: 38 / user set-up: 128)
Attenuation	Available range: 0.1 - 20 dB
APPLICABLE FIBER (CABLE)	
Fiber type	SM (ITU-T G652 & G.657) MM (ITU-T G.651) DS (ITU-T G.653) NZDS (ITU-T G.655)
Coating diameter	100 - 3000 µm
Cladding diameter	80 - 150 µm
Cleaved length	Coating < 250 µm: 10 – 16 mm Coating ≥ 250 µm: 16 mm
HEATING	
Average time	10 s
Modes	41 modes (pre-set: 9 / user set-up: 32)
Applicable sleeve	20 - 60 mm
HARDWARE	
Connectivity (PC link)	USB Mini-B (5-pin)
Electrode lifespan	> 5500 arcs
Data storage	Splice records: 10 000 / image: 2000
Fiber detection	Dual CCD camera with LED emission system
Illumination	LED spotlight
Display	4.3" color LCD with touchscreen (tempered glass)
Battery	Li-Ion 11.1 V 5200 mAh 300 cycles (splicing & heating) Storage temperature: -20 - 40 °C
Power supply	AC 100 - 240 V or DC 12,6 V 1,8 A
Fiber display (magnetification)	Single image (X/Y): 320x Dual image (X&Y): 320x / 400x partial enlargement
Weight	1.5 kg (with battery: 1.9 kg)
Dimensions	124 x 123 x 138 mm (L × W × H)
RELIABILITY	
Wind protection	Maximum wind speed: 15 m/s
Operating environment	Altitude: 0 - 5000 m Temperature: -10 - 50 °C Humidity: 0 - 95 % RH
Storage conditions	Temperature: -40 - 80 °C Humidity: 0 - 95 % RH
Pull test	1,96 - 2,25 N (standard)



ORDERING INFORMATION

Article number	228401

SpliceXpert FiberFox MINI6S+

Scope of delivery:

1 FiberFox MINI6S+ splicer (1)
1 Cleaver 60A (2)
(High-quality fiber cutter with counter, automatic pre-tensioning, and fiber residue removal)
1 Stripper pliers (3-hole) (3)
1 Crimp splice press holder (4)
1 Crimp splice press (Telent) (5)
1 AC power supply unit (6)
1 12V car adapter cable (7)
1 Cooling holder for shrink splice protection (8)
1 Pair of spare electrodes (9)
4 Removable fiber holders - 2 x 250 µm and 2 x 900 µm (10/11)
2 Rechargeable batteries (12)
1 Carrying strap (13)
1 CD with user manual (14)
1 USB upgrade cable (15)
1 USB data cable (16)
1 Robust carrying case with work surface (17)
2 Universal fiber holders (not pictured)

You can find additional accessory offers on our website, or contact us:

itnetworks.softing.com/contact

For more information please contact:

©2025 Softing IT Networks GmbH. In line with our policy of continuous improvement and feature enhancement, product specifications are subject to change without notice. Subject to errors and alterations. All rights reserved. Softing and the Softing logo are trademarks of Softing AG. All other cited trademarks, product and company names or logos are the sole property of their respective owners.

v2.0925

HEADQUARTER
Softing IT Networks GmbH
Richard-Reitzner-Allee 6
85540 Haar, Germany

+49 89 45 656 660
info.itnetworks@softing.com
itnetworks.softing.com